

Absence of  
active  
ingredient  
contaminant  
Antifouling

HACCP\*

# PROTECTION AND DECORATION OF BARREL HOOPS



Sanitary Protection of hoops on barrels and large  
containers

**DEPRO® CERCLAGE VITI**



Barrel chime / croze



## PRODUCT DESCRIPTION

Antifouling paint designed for protection and decoration of hoops on barrels and large containers.  
**Complies with practices outlined in EU Regulation n°852 of April 29th 2004 on the hygiene of foodstuffs. In compliance with HACCP\* practices.**

**In compliance with the "Good Hygiene Practices Guide for the Wine Industry".**

**Research and Development / Scientific Input**

**Confirmation of absence of contamination in liquid products: VECT'OEUR Laboratory.**

## USE

Decorative and sanitary protection for hoops used in cooperage.

## AVANTAGES

- All RAL system colours. Ask us about Châteaux colours.
- The use of an anti-adherent ingredient allows for simple, effective and quick cleaning and decontamination of surfaces.
- Excellent resistance to humid abrasion.



## INSTRUCTION FOR USE

**Application surface preparation:** the surface should be clean, dry, in good condition and free from any substance that may prevent the product from adhering to it.

Surfaces and their preparation should conform to DTU regulation 59.1, standards NFP 7420 1 and 2

**Application: stir wall before use.** DEPRO® CERCLAGE VITI is a mono-component product, easily applied in 1 or 2 coats.

**Application temperature:** min. surface temp. 7°C - max surface temp. 30°C.

**Dilution:** DILUANT SALISTOP VITI (5 to 10 %).

**Application tools:** brush, roller, pistol airless, pneumatic paint gun.

**Drying:** at 20°C and at 65 % HR – Touch-dry: 4 - 6 hours – Ready for Re-coating: 12 - 24 hours.

**Easy to maintain:** clean the finished surface normally as soon as dirt or other marks appear.

## PRODUCT SPECIFICATIONS

- |                      |  |                       |                 |
|----------------------|--|-----------------------|-----------------|
| • Yield              | : 8 - 10 m <sup>2</sup> kg / coat (layer).                           | Finished appearance   | : Bright satin. |
| • Density            | : 1.20 (+/- 0.05)  | Dry extract in weight | : 61(+/- 3%).   |
| • Flash of lighting  | : 38°C.  | Packaging             | : 5 or 25 kg.   |
| • Storage            | : Keeps for 12 months in original unopened container away from cold. |                       |                 |
| • Hygiene and safety | : Safety data sheet available for free on request.                   |                       |                 |

(\*) HACCP: Hazard Analysis and Critical Control Points

Important: The information provided in this document does not in any way constitute a guarantee on the part of the manufacturer, and does not constitute any exemption from the Terms and Conditions stated on the reverse of our Purchase Orders. It is the user's responsibility to attempt trial applications before each use and to follow the recommendations on the product information sheet. Under no circumstances does the manufacturer assume responsibility for the user. It is the user's responsibility to check that the information provided in this document is still accurate at the time of using the product. Product yields depend on the conditions of application and the absorbency of the work surface, and may vary by a margin of 20-30%.

Ref: 04144

06/15

# DEPROMA VITI



15, avenue Foch - B.P. 80032 - 18201 ST AMAND MONTROND Cedex  
Tel: (+33) 02.48.62.01.50 – Fax: (+33) 02.48.96.36.13  
e-mail: info@deproma-viti.com



HYGIENE QUALITY