Sanitary protection

Quick drying







Barrel Chime protection

COOPERAGE VARNISH



Sanitary and alimentary protection for barrels and large

containers.

DEPRO® VERNIS TONNELIER T+

Free from pentachlorophenol





Traditional varnish style Gloss, satin or matt

DESCRIPTION

Water Based Cooperage varnish designed for protection and decoration of barrels and large containers. Protection for barrel chimes and crozes. Traditional varnish appearance - high gloss, satin or mat In compliance with the "Good hygiene practices guide for the wine industry" and practices outlined in EU Regulation n°852 of April 29th 2004 on the hygiene of foodstuffs. Certificate of Analysis from the POURQUERY Laboratory No.RJ11571/0 and RJ11572/0 Tested on materials placed in contact with foodstuffs. Complete Phthalate analysis. Test report and conditions provided upon request.

USES

Sanitary and alimentary protection for all materials used in the handling and transport of products for human consumption which are aqueous, acidic and alcoholic.

ADVANTAGES

- In compliance with HACCP* practices.
- Microporous product, allowing surfaces to preserve their transference properties.
- Excellent resistance in humid conditions.

INSTRUCTIONS OF USE

Surface preparation: the surface should be clean, dry, in good condition and free from any substance that may prevent the product from adhering to it. Surfaces and their preparation should conform to DTU regulation 59.1, standards NFP 7420 1 and 2 Stir well before use.

Application temperature: Min. surface temp. 7°C - Max surface temp. 30°C.

Application: DEPRO® VERNIS TONNELIER T+ is a mono-component product and is easily applied in 1 or 2 coats. Application tools: brush, roller, spray gun (at 5% dilution of Water).

Drying at 20°C (at 65% RH): Dust-dry: 2 hours Dry: 3-4 hours. Set: 24 hours.

Easy to maintain: clean the finished surface normally as soon as dirt or other marks appear. New and old wood: sand to an even surface and remove loose particles.

PRODUCT SPECIFICATIONS

- Yield •
- : 7 to 9 m²/kg.
 - AFNOR : 5 and 20 kg containers
- Packaging Final appearance
- : Family 1, class 6a : Colourless gloss, satin or traditional matt.

Densitv

: 1.03 (+/- 0,1).

: Keeps for 12 months in original unopened container away from cold and heat. Shelf life Hygiene and safety : please refer to our free Safety Guidelines document, available upon request or on our website: www.deproma-viti.com.

Important: The information provided in this technical sheet can not constitute, in any way, a guarantee on our part and do not involve any derogation from our terms and conditions shown on back of our order. It is the responsibility of the user to perform preliminary test prior to each type of use and to follow the method of use in the product data sheet. Our responsability, in any case, cannot replace to that of the user. It belongs to the user to check that the product data sheet sheet is still on effect at the date of application of the product. Yield data depend on application conditions, absorption of relief, surfaces, and can vary from 20 to 30% Ref 05114 feb-19





15, avenue Foch - B.P. 80032 - 18201 ST AMAND MONTROND Cedex Tel: (+33) 02.48.62.01.50 - Fax: (+33) 02.48.96.36.13 e-mail: info@deproma-viti.com